




US 20200098190A1

(19) **United States**(12) **Patent Application Publication**
Goergen et al.(10) **Pub. No.: US 2020/0098190 A1**(43) **Pub. Date: Mar. 26, 2020**(54) **MODULAR AUGMENTED AND VIRTUAL
REALITY RIDE ATTRACTION**(71) Applicant: **Universal City Studios LLC**, Universal
City, CA (US)(72) Inventors: **Patrick John Goergen**, Orlando, FL
(US); **Danielle Marie Holstine**, Winter
Garden, FL (US); **Tomas Manuel
Trujillo**, Orlando, FL (US)(21) Appl. No.: **16/580,543**(22) Filed: **Sep. 24, 2019****Related U.S. Application Data**(60) Provisional application No. 62/736,433, filed on Sep.
25, 2018.**Publication Classification**(51) **Int. Cl.**
G06T 19/00 (2006.01)
H04L 29/08 (2006.01)
G06F 3/01 (2006.01)
A63F 13/211 (2006.01)**A63F 13/843** (2006.01)**A63F 13/26** (2006.01)(52) **U.S. Cl.**CPC **G06T 19/006** (2013.01); **H04L 67/12**
(2013.01); **A63F 13/26** (2014.09); **A63F**
13/211 (2014.09); **A63F 13/843** (2014.09);
G06F 3/011 (2013.01)(57) **ABSTRACT**

An amusement park system includes a modular attraction system having a ride vehicle having seats to accommodate passengers, an on-board system integrated with the ride vehicle and having on-board game systems connected via a network. Each on-board game system is configured to provide an augmented reality (AR) experience, or a virtual reality (VR) experience, or both, via a respective visual experience generator device. The AR experience, or the VR experience, or both, is provided within a game shared between the on-board game systems. The on-board game systems are integrated into the ride vehicle, and are connected via the network to one another in a manner that allows for ready removal of all or a portion of one of the on-board game systems without affecting operation of the remaining on-board game systems.






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8

MODULAR AUGMENTED AND VIRTUAL REALITY RIDE ATTRACTION

CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application claims priority from and the benefit of U.S. Provisional Application Ser. No. 62/736,433, entitled “MODULAR AUGMENTED AND VIRTUAL REALITY RIDE ATTRACTION,” filed Sep. 25, 2018, which is hereby incorporated by reference in its entirety for all purposes.

BACKGROUND

[0002] The subject matter disclosed herein relates to amusement park attractions, and more specifically, to providing augmented experiences, virtual reality experiences, or both, in amusement park attractions.

[0003] Amusement parks or theme parks may include various attractions to provide entertainment to guests (e.g., families and/or people of all ages). For example, the attractions may include a ride, such as a roller coaster, a stationary ride with a motion platform, a dark ride, and so forth. In addition, there may be themed environments along the rides. Such themed environments may be traditionally established using equipment, furniture, building layouts, props, decorations, and so forth. Depending on the complexity of the themed environment, it could prove to be very difficult and time-consuming to setup and replace the themed environment. It may also be very difficult to setup a themed environment that is entertaining for all passengers on the ride. For example, the same themed environment may be appealing to some passengers, but not others.

[0004] In addition, as entertainment technology continues to improve in a variety of settings, such as through developments in the video gaming and movie industries, guests may begin to expect more immersive experiences reflective of state of the art technologies. Depending on the complexity and the level of usage of certain amusement attractions, some of which serve thousands of guests every day, it may be very difficult to modify, upgrade, replace, or maintain functionalities of such attractions.

BRIEF DESCRIPTION

[0005] Certain embodiments commensurate in scope with the present disclosure are summarized below. These embodiments are not intended to limit the scope of the disclosure, but rather these embodiments are intended only to provide a brief summary of possible forms of present embodiments. Indeed, present embodiments may encompass a variety of forms that may be similar to or different from the embodiments set forth below.

[0006] In one embodiment, an amusement park system includes a modular attraction system having a ride vehicle having seats to accommodate passengers, an on-board system integrated with the ride vehicle and having on-board game systems connected via a network. Each on-board game system is configured to provide an augmented reality (AR) experience, or a virtual reality (VR) experience, or both, via a respective visual experience generator device. The AR experience, or the VR experience, or both, is provided within a game shared between the on-board game systems. The on-board game systems are integrated into the ride vehicle, and are connected via the network to one another in

a manner that allows for ready removal of all or a portion of one of the on-board game systems without affecting operation of the remaining on-board game systems.

[0007] In another embodiment, a modular amusement park ride vehicle includes a body having a passenger compartment and seats to accommodate passengers, and on-board game systems each associated with a respective seat to allow each passenger of the modular amusement park ride vehicle to participate in an augmented reality (AR) and/or virtual reality (VR) game shared between the on-board game systems. Each on-board game system includes a gaming computer configured to render AR or VR graphics, and a head-mounted display (HMD) in communication with the gaming computer and configured to display the AR or VR graphics. The vehicle also includes an on-board game server configured to coordinate communication with the on-board game systems via an on-board network switch individually connected to the on-board game systems, and a vehicle show supervisor (VSS) communicatively coupled to the on-board game server and configured to receive game inputs from the passengers relating to the AR and/or VR game. The VSS is configured to relay the game inputs to the on-board game server via the on-board network switch.

[0008] In another embodiment, an amusement park attraction system includes an on-board system integrated with a ride vehicle. The on-board system has a visual experience generator device for each seat in the ride vehicle, and the on-board system is configured to provide an augmented reality (AR) experience, virtual reality (VR) experience, or both, within a shared game via at least the visual experience generator devices. The amusement park attraction system also includes an off-board system communicatively coupled to the on-board system via a network and having off-board show devices positioned off of the ride vehicle. The off-board system includes an off-board game server communicatively coupled to the off-board show devices and configured to coordinate operation of the off-board show devices with AR or VR events occurring during the shared game.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] These and other features, aspects, and advantages of the present disclosure will become better understood when the following detailed description is read with reference to the accompanying drawings in which like characters represent like parts throughout the drawings, wherein:

[0010] FIG. 1 is a schematic view of an embodiment of an amusement park having a modular architecture, in accordance with certain aspects of the present disclosure;

[0011] FIG. 2 is a block diagram of an embodiment of the modular architecture that may be used in the amusement park of FIG. 1, in accordance with certain aspects of the present disclosure;

[0012] FIG. 3 is a perspective view of an embodiment of a modular attraction system that includes a ride vehicle with an on-board system that coordinates with an off-board system to provide augmented reality and/or virtual reality (AR/VR) experiences, in accordance with certain aspects of the present disclosure;

[0013] FIG. 4 is a block diagram of an embodiment of the on-board system that may be used with the ride vehicle of FIG. 3, in accordance with certain aspects of the present disclosure;

[0014] FIG. 5 is a block diagram of an embodiment of on-board game systems of the on-board system of FIG. 4, in accordance with certain aspects of the present disclosure;

[0015] FIG. 6 is a perspective view of an embodiment of the ride vehicle of FIG. 3, in accordance with certain aspects of the present disclosure;

[0016] FIG. 7 is a block diagram of an embodiment of the off-board system of the modular attraction system of FIG. 3, in accordance with certain aspects of the present disclosure; and

[0017] FIG. 8 is a block diagram of an embodiment of the on-board system and the off-board system that may be used in the modular attraction system of FIG. 3, in accordance with certain aspects of the present disclosure.

DETAILED DESCRIPTION

[0018] One or more specific embodiments of the present disclosure will be described below. In an effort to provide a concise description of these embodiments, all features of an actual implementation may not be described in the specification. It should be appreciated that in the development of any such actual implementation, as in any engineering or design project, numerous implementation-specific decisions must be made to achieve the developers' specific goals, such as compliance with system-related and business-related constraints, which may vary from one implementation to another. Moreover, it should be appreciated that such a development effort might be complex and time consuming, but would nevertheless be a routine undertaking of design, fabrication, and manufacture for those of ordinary skill having the benefit of this disclosure.

[0019] It is now recognized that it is desirable to include attractions where it may be possible to change attraction themes in a flexible and efficient manner relative to traditional techniques. It is also now recognized that it may be desirable to provide attraction features that readily allow upgrades, maintenance, or replacement of key components in a manner that does not create significant attraction downtime. Indeed, as one example, theme park attractions using ride vehicles have historically had long lead times associated with technical refresh upgrades. Thus, cutting edge technology (e.g., augmented or virtual reality) within these attractions can easily be outpaced by what is available in home consumer products.

[0020] It is presently recognized that a need exists for, among other things, amusement attractions (e.g., ride vehicle systems) to be designed in a way that allows ready integration of technical refreshes, particularly those that follow initial integration of cutting edge technologies. For instance, it is now recognized that a need exists for amusement ride designs that allow updates to be performed agnostically and rapidly for both software and hardware, with minimal impacts to ride aesthetics and operations. To address these and other concerns, the present disclosure provides an architecture that encompasses hardware and software to ensure either can be updated with minimal negative impact to the system.

[0021] As one example embodiment of the present disclosure, an amusement park attraction may include a modular attraction system. The modular attraction system may incorporate an on-board system (e.g., on a ride vehicle) that drives an on-board experience (e.g., an experience local to a user and/or the ride vehicle). For example, the on-board system may provide gaming effects resulting in an aug-

mented reality and/or virtual reality (AR/VR) experience, which may include a visual experience presented by way of one or more display features (e.g., head mounted displays (HMDs)). The modular attraction system may also include an off-board system (e.g., off the ride vehicle) that coordinates certain aspects of various components of the on-board system, and provides other entertainment experiences using light systems, animatronics, media systems (e.g., projection display systems and sound systems), or a combination thereof, associated with the particular amusement park attraction. The on-board and off-board systems may operate collaboratively to enhance the ride experiences of the passengers. In addition, the on-board and off-board systems and their various components are designed in such a way that they may be individually or separately replaced, maintained, modified, upgraded and so forth, with minimal downtime of the amusement park attraction.

[0022] The terms "on-board system" and "off-board system" are used herein to denote two systems that work together to create an overall experience in the amusement park attraction, and it should be appreciated that components of these systems are not necessarily intended to be limited to any particular placement relative to the ride vehicle. For example, in one implementation discussed in detail herein, all of the components of the on-board system may be located on the ride vehicle (e.g., move with the ride vehicle), while all of the components of the off-board system may be located off the ride vehicle (e.g., do not move with the ride vehicle). However, the on-board system may additionally or alternatively include components that are co-located with the ride vehicle (e.g., components that are not located on the ride vehicle, but are in proximity of the ride vehicle during at least a portion of the ride). For example, at least some components of the on-board system may be positioned at a location along a path traversed by the ride vehicle, and these components of the on-board system may communicate (e.g., via a wireless network) with other components of the on-board system that are located on the ride vehicle when the ride vehicle is at or near the location along the path to drive the on-board experience. As another example, the ride vehicle may not physically travel along a path (e.g., may be stationary; move in place, such as rock or rotate without traveling along a path). In some such cases, at least some components of the on-board system may be positioned at a location proximate to the ride vehicle, and these components of the on-board system may communicate (e.g., via a wireless network) with other components of the on-board system that are located on the ride vehicle to drive the on-board experience.

[0023] In yet another example, the attraction may not include a ride vehicle, but instead the user may walk or otherwise travel through the attraction wearing or carrying one or more interactive components, such as the one or more display features (e.g., the HMD), speakers, and/or haptics. In some such cases, all of the components of the on-board system may be worn or carried by the user (e.g., move with the user), while all of the components of the off-board system may be located off of the user (e.g., do not move with the user). However, the on-board system may additionally or alternatively include components that are co-located with the user (e.g., components that are not worn or carried by the user, but are in proximity of the user during at least a portion of the amusement park attraction). In some such cases, at least some components of the on-board system may be

positioned at a location along a path traversed by the user or otherwise proximate to the user, and these components of the on-board system may communicate (e.g., via a wireless network) with other components of the on-board system that are worn or carried by the user when the user is at or near the location along the path to drive the on-board experience.

[0024] Additionally or alternatively, the on-board system may include components that are located remotely from the ride vehicle and the user (e.g., at any location, including outside of physical boundaries of the amusement park attraction), but may communicate (e.g., via a wireless network) with other components of the on-board system that are physically located on the ride vehicle or worn or carried by the user to create the on-board experience, for example. Furthermore, the off-board system may include components (e.g., distinct from the components of the on-board system) that work together with the components of the on-board system to create the overall experience. For example, the off-board system may include components that drive off-board experiences, such as fog, smoke, wind, and/or lights, in an environment surrounding the ride vehicle and/or the user within the amusement park attraction.

[0025] While certain embodiments discussed in detail herein include a visual experience presented via HMDs to facilitate discussion, it should be appreciated that the AR/VR experience may additionally or alternatively include a visual experience presented via any other suitable technology, such as via any other suitable visual experience generator (e.g., a hand-held display, a vehicle-mounted display, a virtual retina display or retinal projector that projects onto a retina of the user) that is capable of generating a visual representation that can be visualized by the user. For example, the HMDs disclosed herein may be replaced with or used in conjunction with any other suitable visual experience generator. Additionally, the AR/VR experience may include the visual experience, an auditory experience presented by way of one or more speaker features, and/or a tactile experience presented by way of one or more haptic features. In some embodiments, the AR/VR experience may include only an auditory experience or only a tactile experience.

[0026] With the foregoing in mind, FIG. 1 illustrates an embodiment of an amusement park 10, which may include one or more attractions 12. Each attraction 12 may accommodate a plurality of users 14 (e.g., guests, patrons). As discussed herein, the amusement park 10 may utilize a multi-layer system infrastructure to accommodate technological refreshes, updates, and so forth, while minimizing downtime and impact of overall aesthetics and operations of the amusement park 10. Particularly, modularity of the multi-layer system infrastructure may provide for a change (e.g., an update, a replacement, an addition, and/or a removal) of one or more hardware or software components without substantially affecting other elements (e.g., other hardware or software components) of the system.

[0027] To illustrate, in certain embodiments, the amusement park 10 may include a first attraction 16, a second attraction 18, and a third attraction 20. However, it should be understood that the amusement park 10 may include any suitable number of attractions 12. Each attraction 12 may include any suitable number of hardware components 22, such as physical components that may use and interact (e.g., communicate) with software components 24, which may be stored in a memory device 26 of one or more controllers 28

to perform tasks associated with a particular attraction 12, as discussed in further detail herein. Indeed, there may be any suitable number of controllers 28. In certain embodiments, each attraction 12 may be associated with a respective controller 28. The amusement park 10 may further include one or more hardware components 22 within an environment 29 (e.g., queues) of the amusement park 10, which may also be communicatively coupled to the one or more controllers 28. In certain embodiments, the environment 29 may include the attractions 12.

[0028] The controller 28 may employ a processor 30, which may represent one or more processors, such as an application-specific processor. The controller 28 may also include the memory device 26 for storing instructions executable by the processor 30 to perform the methods and control actions of the amusement park 10 as described herein. The processor 30 may include one or more processing devices, and the memory 26 may include one or more tangible, non-transitory, machine-readable media. By way of example, such machine-readable media can include RAM, ROM, EPROM, EEPROM, CD-ROM, or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other medium that can be used to carry or store desired program code in the form of machine-executable instructions or data structures and that may be accessed by the processor 30 or by any general purpose or special purpose computer or other machine with a processor.

[0029] The controller 28 may be communicatively coupled to elements of the amusement park 10 through a communication system 32. In some embodiments, the communication system 32 may communicate wirelessly. By way of non-limiting example, such communication may involve a wireless network (e.g., wireless local area networks [WLAN], wireless wide area networks [WWAN]), near field communication [NFC], or Bluetooth. Additionally or alternatively, the communication system 32 may use wired communication, such as a wired network including a local area network [LAN], or wide area network [WAN].

[0030] Each hardware component 22 (e.g., peripheral device) may be categorized as an input device and/or an output device. That is, each hardware component 22 may be an input device, an output device, or an input/output device. An input device may receive an input, such as from one of the plurality of users 14, and send input signals indicative of the received input to the controller 28. The hardware components 22 may include interactive components, and the input may be received via one or more user input devices (e.g., buttons, knobs, touchscreens, joysticks, actuatable elements, steering controls, triggers) of the interactive components. Correspondingly, and as a result of the input signals, the output devices may receive the input signals, which may be received from the controller 28 and/or directly from the input devices. For example, the controller 28 may then, in turn, send one or more signals to one or more locations, such as the output devices, within the amusement park 10 to provide an appropriate response according to the received input. The output devices may react accordingly to the signal, such as through actuation of a device or through display of images/information via a display device or via any suitable visual experience generator. For example, with regard to hardware components 22 of the first attraction 16, input devices may include AR/VR devices, such as AR/VR

tools and head mounted displays (HMDs), and output devices may include the HMDs as images are displayed via the HMDs.

[0031] With regard to the hardware components 22 of the second attraction 18, input devices may include ride devices (e.g., tools) that the users 14 may interact with during a ride cycle and output devices may include animatronic show pieces and ride vehicles. With regard to the hardware components 22 of the third attraction 20, input devices may include steering wheels and output devices may include a scoreboard, and a game floor display. However, it is to be understood that the amusement park 10 may include any suitable number of attractions 12 with any suitable number and type of hardware components 22. Further, AR/VR devices may serve as input/output devices that facilitate user interaction with the attraction 12 to generate the input and cause another hardware element to output a response. In turn, the response may also trigger output changes to the AR/VR devices (e.g., to the display of the AR/VR devices).

[0032] Each of the hardware components 22 and software components 24 may be replaced or updated based on various factors. For example, emerging technologies, movies or other media releases, seasonal change, time of day, routine maintenance, or any combination thereof may motivate a change to the hardware components 22 and/or software components 24 of the amusement park 10. When a component (e.g., a hardware component 22 or a software component 24) is introduced, updated, or otherwise changed within the amusement park 10, the component may be registered with the amusement park 10 such that the component may interact (e.g., communicate) with other components of the amusement park 10. That is, the one or more controllers 28 may include various protocols to send and receive information to and from components of the amusement park 10 as discussed in further detail with reference to FIG. 2.

[0033] Each of the attractions described with respect to FIG. 1 may include modular components that form all or part of a modular attraction system as previously discussed. To illustrate an example of the manner in which such a system may be implemented, FIG. 2 is a block diagram of a system architecture of a modular attraction system 50 of the amusement park 10. The modular attraction system 50 may be separated into a game layer 52, a software layer 54 (e.g., a software architecture layer), and a hardware layer 56 (e.g., a hardware architecture layer). The game layer 52 and the software layer 54 may each be stored within the memory 26 of the controller 28. The game layer 52 and the software layer 54 may be communicatively coupled to the hardware layer 56 via the communication system 32. The game layer 52 may include a game logic 58, which determines logic of when an attraction 12 interacts with, changes, and/or manipulates elements (e.g., hardware components 22 and/or software components 24) of the attractions 12. That is, the game layer 52 may operate and execute game logic 58.

[0034] The software layer 54 may include one or more game application programming interfaces (APIs) 60, one or more wrapper APIs 62, and multiple wrappers 64. The game API 60 may define an interface language set that any game implementation (e.g., game logic 58 of a particular attraction 12) can use to communicate with the software layer 54 and the hardware layer 56. For example, the game logic 58 may communicate with the game API 60 to trigger various environmental stimuli (e.g., reactions carried out through the hardware components 22) within the amusement park 10.

[0035] The wrapper API 62 may route messages from the game API 60 to the wrappers 64. The wrappers 64 are software elements that conform, extend, and/or implement a standard interface class and are configured to register with the wrapper API 62 to receive the messages associated with the environmental stimuli. The wrappers 64 may communicate with a driver associated with a particular hardware component 22 so that the hardware component 22 may receive the messages associated with environmental stimuli. In certain embodiments, each hardware component 22 may be associated with one or more respective wrappers 64. The wrappers 64 may serve as a buffer between the hardware components 22 of the hardware layer 56 and the software components 24 of the software layer 54. For example, when the hardware components 22 are updated or changed, the change or update will not impact operations, logic, and/or builds of the software components 24. Conversely, as software components 24 are updated, the wrappers 64 may reduce and/or prevent the need to update the hardware components 22 to be compatible with the updated software components 24. In certain embodiments, additional hardware components 22 or features may be added. In such embodiments, one or more wrappers 64 associated with the newly added hardware components may also be added to the software layer 54. The newly added wrappers 64 may then be registered with the wrapper API 62 to allow proper communication of signals (e.g., messages, events).

[0036] The hardware layer 56 may include the hardware components 22 which, as discussed herein, are configured to be readily replaceable and/or updatable. That is, the hardware components 22 may utilize a modular design (e.g., composed of standardized units), standard (e.g., universal) mounting points, and dynamic internal configurations to improve implementation of new hardware components 22 and updates to existing hardware components 22. For example, the hardware components 22 may utilize a general purpose interface bus (GPIB) 70 (e.g., general purpose interface (GPI)), which may form part of the communication system 32, to communicate with components within the software layer 54 and other hardware components 22 within the hardware layer 56. Indeed, in certain embodiments, the hardware components 22 may utilize wired and/or wireless communication. In some embodiments, the hardware components 22 may communicate without the use of a network, such as by direct or broadcast communications through wired and/or wireless means.

[0037] As a further example, the hardware components 22 may utilize and/or be a line replaceable unit (LRU) 72, which is a modular component that is readily replaceable at the operating location of the unit. Particularly, the LRU 72 may be quickly replaced at the attraction 12 (e.g., “on the line”), which may provide for decreased downtime of the attraction 12. Indeed, the hardware components 22 within the hardware layer 56 may utilize, for example, a limited number (e.g., one) of standards associated with various components, such as power supply standards, input and output module standards, and others. In this manner, if a portion (or all) of a hardware component 22 should be added or changed, the portion may easily be implemented due at least in part to the standard (e.g., general, universal, modular) components. The modular design of the hardware components 22 may be based on standards, guidelines, and best practices to ensure correct implementation. In certain embodiments, the hardware components 22 may provide

self-testing. That is, the hardware component 22 may determine if it is suitable to continue operation. For example, the hardware component 22 may include one or more sensors 73 configured to monitor inputs and outputs of the hardware component 22 to determine the operational status of the hardware component 22, such as whether the hardware component 22 is operating as intended and/or if a part within the hardware component 22 should be replaced/updated, such as if the hardware component 22 is nearing an end of its product lifecycle.

[0038] An example embodiment of the modular attraction system 50 within the amusement park 10 is shown schematically in FIG. 3. As illustrated, the amusement park 10 may include a ride 80 as the second attraction 18. The ride 80 may be positioned within the environment 29 having various features, such as fixed equipment, building layouts, props, decorations, and so forth, corresponding to a theme. In certain embodiments, the ride 80 may include a dark ride or other similar thrill ride, and may include a ride path 82 (e.g., a closed-loop track or a system of closed-loop tracks to support forward and/or rearward motion of a ride vehicle 84 along the ride path 82; vertically-extending track to support vertical motion of the ride vehicle 84 along the ride path 82). The ride path 82 may be provided as an infrastructure on which the ride vehicle 84 may travel as users 14 are accommodated by the ride vehicle 84. The ride path 82 may thus define the motion of the ride vehicle 84. However, in another embodiment, for example, the ride path 82 may be replaced by a controlled path, in which the movement of the ride vehicle 84 may be controlled via an electronic system, a magnetic system, or other similar system infrastructure other than the ride path 82. In other words, the ride path of the ride vehicle 84 may not be physically constrained to an exact path, thereby allowing the users 14 some degree of control over their motion path, view perspective, and so forth. Other amusement park attractions may be positioned sufficiently proximate to the ride 80 to allow the users 14 a view of the attractions. By way of example, such attractions may include buildings 86 or similar structures.

[0039] It should be appreciated that while the ride vehicle 84 may be illustrated as a 4-passenger vehicle, in other embodiments, the ride vehicle 84 may include any number of passenger spaces (e.g., 1, 2, 4, 8, 10, or more spaces) to accommodate a single or multiple groups of passengers. It should also be appreciated that while the ride 80 may be illustrated having one ride vehicle 84, the ride 80 may include any number of ride vehicles 84 (e.g., 1, 2, 4, 8, 10, or more). As the ride vehicle 84 travels along the ride path 82, the users 14 may be provided a moving tour of the scenery (e.g., themed environment that may include fixed equipment, building layouts, props, decorations, and so forth corresponding to the theme). The scenery may include the environment surrounding the ride 80 and/or the environment within an infrastructure that may fully or partially house the ride 80.

[0040] While the users 14 may find the ride 80 to be a very enjoyable experience, in certain embodiments, it may be useful to enhance their ride experience. Specifically, the ride experience provided to the users 14 may be enhanced with gaming effects and other entertainment (e.g., multimedia entertainment) provided by the modular attraction system 50. In the illustrated embodiment, the modular attraction system 50 includes an on-board system 88 integrated with the ride vehicle 84 and an off-board system 90, which

together are configured to provide augmented reality and/or virtual reality (AR/VR) experiences to the users 14 by way of head mounted displays (HMDs) 92 and/or other devices (e.g., other visual experience generators, speakers, haptic features). For example, as the ride vehicle 84 travels along the ride path 82, the modular attraction system 50, via the on-board system 88, may coordinate AR/VR images or features, such as AR/VR objects 94 (shown as a clown floating over the buildings 86), to be shown to the users 14 on their respective HMDs 92. The off-board system 90 may include various physical features such as displays, animatronics, and so forth. The operation of these devices may be coordinated with the visualizations presented on the HMDs 92.

[0041] Indeed, as set forth above, the modular attraction system 50 may coordinate the on-board system 88 and the off-board system 90 to collectively and collaboratively enhance the ride experience of the users 14. In certain embodiments, all or a portion of the off-board system 90 may be disposed along the ride path 82. For example, as the ride vehicle 84 travels along the ride path 82, the modular attraction system 50, via the off-board system 90, may coordinate visual and/or audible media provided by way of light systems, sound systems, animatronics, display systems, or any combination thereof, disposed along the ride path 82. The modular attraction system 50 may utilize the communication system 32, for example communication devices such as servers, routers, communication modules, antennas, and so forth, in the on-board system 88 and/or the off-board system 90 to facilitate provision of various show features to the users 14. The on-board system 88 and the off-board system 90 may communicate, for instance, over a network 96 to allow for coordination between on-board show events and off-board show events.

[0042] In the illustrated embodiment, for instance, the off-board system 90 includes an automated prop 98 that is controlled by features of the off-board system 90 in coordination with the on-board system 84. More specifically, as shown, the animated prop 98 is a cannon that shoots darts. The movement of the cannon, as well as air effects (e.g., air blasts), sound and/or light effects, and so forth provided by the cannon may be coordinated with rendering and display of the clown (AR object 94). For instance, by coordinating operation of the on-board system 88 and the off-board system 90, the cannon (automated prop 98) may seem to track the clown and the clown's balloons to seemingly shoot the balloons with darts to pop them and allow the clown to return to the ground.

[0043] As noted above, while the on-board system 88 is shown in FIG. 3 as being positioned on the ride vehicle 84, the components of the on-board system 88 may be placed in various locations relative to the ride vehicle 84 (e.g., placed along the ride path 82 to be co-located with the ride vehicle 84 during at least a portion of the ride). The modular attraction system 50 may also be used with other types of attractions, including attractions with stationary ride vehicles that do not travel along a ride path and/or attractions without ride vehicles.

[0044] In accordance with present embodiments, and as noted above, features of the on-board system 88, features of the off-board system 90, or any combination thereof, may be designed to readily allow maintenance and technical refreshes. For example, updated technologies may enable a

more realistic simulation of the clown, darts, and so forth. FIGS. 4-7 depict example architectures to achieve refresh-ready designs.

[0045] FIG. 4 is a block diagram of various components of the on-board system 88 of the modular attraction system 50. In the illustrated embodiment, the on-board system 88 is a dedicated system disposed on or integrated with the ride vehicle 84. It should be appreciated that the on-board system 88 may be integrated with the ride vehicle 84 such that all of the components of the on-board system 84 are physically located on the ride vehicle 84 (as shown in FIG. 4), or the on-board system 88 may be integrated with the ride vehicle 84 such that at least some components of the on-board system 88 are physically located on the ride vehicle 84 and at least some components of the on-board system 88 are physically located off of the ride vehicle 84 (e.g., physically separated from the ride vehicle 84). For example, the on-board game server 114 may be located off of the ride vehicle 84 and may communicate with the other components of the on-board system 88 via the network 96 to drive the on-board experience.

[0046] Additionally, as noted above, the attraction may not include a ride vehicle, but instead the user may walk or otherwise travel through the attraction wearing or carrying one or more interactive components, such as the one or more display features (e.g., the HMD), speakers, and/or haptics. In some such cases, all of the components of the on-board system 88 may be worn or carried by the user (e.g., move with the user), while all of the components of the off-board system 90 may be located off of the user (e.g., do not move with the user). However, the on-board system 88 may additionally or alternatively include components that are co-located with the user (e.g., components that are not worn or carried by the user, but are in proximity of the user during at least a portion of the amusement park attraction). In some such cases, at least some components of the on-board system may be positioned at a location along a path traversed by the user or otherwise proximate to the user, and these components of the on-board system 88 may communicate (e.g., via a wireless network) with other components of the on-board system 88 that are worn or carried by the user when the user is at or near the location along the path to drive the on-board experience. Furthermore, some components of the on-board system 88 may be located remotely from the user and/or the ride vehicle 84.

[0047] As shown in FIG. 4, the on-board system 88 may include a local network established using a central network switch 110 (e.g., an “on-board” network switch), which is configured to manage, or allow for management, of communications between various features of the on-board system 88. The switch 110 is configured to allow for communication between the on-board system 88 and the network 96 via a network communication device 112. In certain embodiments, the switch 110 and the network communication device 112 may be integrated together in a single device (e.g., communication device). As an example, the switch 110 may be a router or similar device and the network communication device 112 may be a modem or similar device. It should be appreciated that the on-board system 88 may include any suitable communication component(s) that enable communication between the on-board system 88 and the network 96.

[0048] In accordance with present embodiments, the network communication device 112 and the switch 110 may be

separate, but may utilize standardized communication protocols and connectors to facilitate connection with a wide variety of devices. In the illustrated embodiment, for example, the switch 110 has an internal network connection (internal to the on-board system 88) with the on-board game server 114, the VSS 116, and one or more on-board game systems 118, for example by way of one or more communications buses, cabling, or wireless devices. These features are described in further detail below.

[0049] The on-board game server 114, the vehicle show supervisor (VSS) 116, and the one or more on-board game systems 118, as illustrated, are connected to various devices on board the ride vehicle 84 and/or to one another. These connections are intended to indicate one or more communications connections, power connections, and so forth. Further, it should be noted that while only one block is used for certain components, such components may be present as multiple devices and are designated with an asterisk. For example, while the on-board game systems 118 is shown as a single box, this single box may, in certain embodiments, represent a series of features (a plurality of on-board game systems) that are redundantly in place for each of the positions corresponding to one of the users 14 (e.g., each seat of the ride vehicle 84). Again, in the context of the ride vehicle 84, it should be noted that the user 14 is intended, in some embodiments, to denote a passenger of the ride vehicle 84. Other illustrated features that may be redundantly present include tracking sensors 120 and user interfaces 122.

[0050] One or more tracking systems 124 are illustrated as connected to the one or more tracking sensors 120. The tracking system 124 may include a special-purpose computing device disposed on or integrated with the ride vehicle 84 to process data generated by the tracking sensors 120 indicative of the positions, locations, orientations, presences, and so forth of the HMDs 92, the users 14, the ride vehicle 84, or any combination of these. The tracking system 124 may be configured to interface with a variety of tracking devices, and is programmed to receive data from the tracking sensors 120 and to process this data to provide tracking information to the on-board game server 114. Indeed, the tracking system 124 may have a direct network connection to the on-board game server 114 to minimize latency between the reception of tracking data and concomitant responses by the various features of the on-board system 88 and/or off-board system 90. Further, this direct connection may facilitate technical refreshes and maintenance since the manner in which the tracking data may be used by the on-board system 88 is not necessarily dependent on any of the other devices present in the system.

[0051] The tracking sensors 120 may include orientation and position sensors (e.g., accelerometers, magnetometers, gyroscopes, Global Positioning System [GPS] receivers), motion tracking sensors (e.g., electromagnetic and solid-state motion tracking sensors), inertial measurement units (IMU), presence sensors, and others. In some embodiments, the tracking sensors 120 may be disposed on or integrated with the HMDs 92 and thus are configured to generate data representative of the motion and orientation of the HMDs. Indeed, the data received by tracking system 124 may be useful in determining each user's gaze direction, viewing perspective, field of view, viewing interest, interaction with the game, and so forth. Additionally or alternatively, the tracking system 124 may also use data generated by the tracking sensors 120 to track operational information of the

ride vehicle **84**, including but not limited to, a position, orientation, velocity, motion vector, or other parameter of the ride vehicle **84**.

[0052] As set forth previously, the user interfaces **122** may be present for each of the users **14** to allow each user **14** some level of control over their experience. In certain embodiments, the one or more user interfaces **122** may be disposed on or integrated with each seat or passenger space of the ride vehicle **84**. The one or more user interfaces **122** may include analog and digital devices, such as handheld controllers, joysticks, push buttons, steering wheels, and so forth. For example, the one or more user interfaces **122** may be configured to enable different actions and/or effects to be applied in the AR/VR environment established on the HMDs **92** using other features of the on-board game systems **118**. For example, the one or more user interfaces **122** may allow the user **14** to affect a character or an object of the AR/VR features in different directions (e.g., up, down, left, right) in the AR/VR environment. By way of more specific but non-limiting example, the one or more user interfaces **122** may allow the passenger to make selections or grab/release objects of the AR/VR features in the AR/VR environment. In some embodiments, the one or more user interfaces **122** may allow the user **14** to control operation of the ride vehicle **84**, such as changing its velocity and/or direction. In some embodiments, the one or more user interfaces **122** may also include one or more display screens and/or touch screens to allow information to be communicated to the user **14**.

[0053] The user interfaces **122** may be directly coupled to the VSS **116**, which may be a programmable logic controller (PLC), or other suitable control device. For instance, the VSS **116** may include a processor (e.g., a general-purpose processor, a system-on-chip (SoC) device, an application-specific integrated circuit (ASIC), or some other similar processor configuration) operatively coupled to a memory (e.g., a tangible non-transitory computer-readable medium and/or other storage device) to execute instructions stored in the memory. The VSS **116** may be considered to be one of the controllers **28** shown in FIG. 1.

[0054] The VSS **116**, generally, may be configured to coordinate various operations of the on-board system **88** in response to user inputs and in response to instructions provided by the on-board game systems **118** and the off-board system **90**, for example due to execution of game logic. In the illustrated embodiment, the VSS **116** is communicatively coupled to the one or more on-board game systems **118** and the one or more user interfaces **122**, such that information may be provided to and from the one or more user interfaces **122** and the one or more on-board game systems **118**. The VSS **116** may also provide power to the one or more user interfaces **122** and the one or more on-board game systems **118**, as appropriate.

[0055] By way of non-limiting example, the VSS **116** may have a number of voltage connections to the on-board game systems **118** for power-on commands, reset commands, and for power indications from the on-board game systems **118**. For instance, during operation the VSS **116** may send signals to reset and/or to change on/off states of the one or more on-board game systems **118**. Similar connections may also be present between the VSS **116** and the user interfaces **122**. In embodiments where the one or more user interfaces **122** include one or more display screens and/or touch screens, the VSS **116** may control a power state of the device, timing of the device, certain content (e.g., displayed content), and

so forth. Other vehicle show effect devices **126** may also be connected to, powered, and controlled by the VSS **116**. By way of example, such devices **126** may include vehicle lights, automated devices of the ride vehicle **84**, effect devices of the ride vehicle **84** (e.g., air cannons, water cannons), and so forth.

[0056] As illustrated and noted above, the VSS **116** has one or more direct connections to the on-board game systems **118** to allow for power cycling, power state control, and so forth. However, the VSS **116** may also control other devices responsible for motion of the ride vehicle **84**. For example, the VSS **116** may control steering features (e.g., axles, wheels) in response to inputs from the user interfaces **122**, and in response to data received from the on-board game server **114** relating to other ride vehicles **84**, off-board show elements, and so forth.

[0057] Indeed, in a given ride attraction, there may be multiple ride vehicles **84**, each having a corresponding set of devices. To facilitate coordination between these devices and because the inputs from multiple users **14** may be used to update each user's experience, inputs from the user interfaces **122**, rather than simply being provided directly to the on-board game system **118** corresponding to an individual user, may instead be provided to the network **96** via the local network connection between the VSS **116** and the switch **110**. Provision of such inputs, as noted above, may be controlled by the on-board game server **114**. In such embodiments, each user's inputs are coordinated and communicated over the local network of the ride vehicle **84** and the network **96**, which allows rapid communication with low latency because the inputs are not processed (or are minimally processed) before they are received by the individual on-board game systems **118** and the VSS **116**. It should be appreciated that some or all of capabilities of the VSS **116** disclosed herein may be included in another processing component (e.g., processing or computing system) of the on-board system **88**, such as in the on-board game server **114**.

[0058] As there are multiple on-board game systems **118**, each controlled in accordance with inputs from multiple user input devices **122**, the architecture shown in FIG. 4 allows for ready replacement, maintenance, and updates to be performed on them individually without requiring corresponding activities to be performed on other input devices **122** or other on-board game systems **118**. Further, this type of connection and communication scheme may also reduce latency in graphical rendering activity performed by the on-board game systems **118**, for example in response to user inputs.

[0059] To allow for the coordinated and controlled data communication set forth above, the on-board game server **114** may include a special-purpose computing device (e.g., a specially-programmed computing device) that is programmed to coordinate how information is transmitted and received on the network **96** with respect to the ride vehicle **84**. That is, the on-board game server **114** may coordinate network data traffic for the ride vehicle **84**, including data that is transmitted over the network **96** to and from the off-board system **90** and to other ride vehicles **84**. This may be done, for example, to ensure that certain types of data are prioritized over others according to an information hierarchy (e.g., a communication hierarchy). The on-board game server **114** may include one or more programmable logic controllers (PLCs), or other suitable control devices. Addi-

tionally or alternatively, the on-board game server **114** may include a processor (e.g., a general-purpose processor, a system-on-chip (SoC) device, an application-specific integrated circuit (ASIC), or some other similar processor configuration) operatively coupled to a memory (e.g., a tangible non-transitory computer-readable medium and/or other storage device) to execute instructions stored in the memory. In certain embodiments, the on-board game server **114** is a server computer which may also include standardized communications ports to allow for ready integration of new, replacement, or repaired devices, and may be programmed to communicate in accordance with appropriate standards (e.g., proprietary standards, IEEE standards).

[0060] As noted, the on-board game server **114**, generally, may be configured to coordinate communication of various information between the on-board system **88** and the off-board system **90**, and also between the various components of the on-board system **88**. In particular, the various information may be routed via the switch **110**. As also previously noted, the switch **110** is generally a router or any suitable networking device that forwards information (e.g., data packets) to destination nodes (e.g., the various devices of the on-board system **88**) or computer networks, so as to perform the traffic directing functions on the network (e.g., the communication network **96** and the local network of the ride vehicle **84**). As an example, the on-board game server **114** may direct information between the one or more tracking systems **124**, the one or more on-board game systems **118**, and the VSS **116**, via the switch **110**.

[0061] In addition, the on-board game server **114** may be configured to coordinate or synchronize communication of information depending on the information type (e.g., information priority). By way of example, the on-board game server **114** may determine or have stored relative priorities of the different types of information and communicate such information based on their relative priorities. In an example information hierarchy, information related to operations of the ride **80** may be a first type, information related to generation of the game and entertainment experiences may be a second type, and so forth. By way of more specific example, information that may ensure or affect operations and/or safety of the ride **80** may have the highest priority, information that conveys game-related notifications or game-related information may have the second highest priority, and so forth.

[0062] In some embodiments, the on-board game server **114** may communicate information determined as having the highest priority before communicating other information determined as having a lower priority. In a practical sense, for example, if one ride vehicle **84** is identified as being stopped, this information would be communicated to other ride vehicles **84** (e.g., to allow for emergency stops of the remaining ride vehicles **84**) before other information (e.g., game information) is transmitted.

[0063] In some embodiments, the on-board game server **114** may communicate information based on their types and relative priorities and other factors, such as the available bandwidth of the network **96**, timing of the game and entertainment experiences, size of the data packet, etc. As such, the on-board game server **114** may coordinate or synchronize the communication of various information effectively and ensure communication of important information.

[0064] The one or more on-board game systems **118**, generally, may be configured to provide game experiences (e.g., AR/VR experiences) to the users **14** via the HMDs **92** and/or other devices (e.g., other visual experience generators, speakers, haptic features). In particular, each seat or passenger space of the ride vehicle **84** may include a dedicated on-board game system **118**, and the plurality of on-board game systems **118** allow for the passengers to participate in a shared game (e.g., a multiplayer game). The one or more on-board game systems **118** will be discussed in more detail in FIG. **5**, which is a schematic diagram of an embodiment of the one or more on-board game systems **118** of the ride vehicle **84** (or multiple ride vehicles **84**).

[0065] As illustrated in FIG. **5**, the one or more on-board game systems **118** may include various features that, as a whole, are configured to provide a gaming experience that is enhanced with AR/VR graphics to one of the users **14**. More specifically, FIG. **5** illustrates a plurality of the on-board game systems **118**, including a first on-board game system **118A**, a second on-board game system **118B**, and so on . . . to an n^{th} on-board game system **118N** (e.g., depending on the number of available seats and corresponding on-board game systems provided by the ride vehicle **84**). Specific components are described herein with respect to the first on-board game system **118A**, but it should be appreciated that similar or the same components may be present in all the on-board game systems **118**. Further, the components described herein may be integrated into the on-board game systems **118** in a manner that is consistent with the approach described with respect to FIG. **2**. It should be appreciated that an on-board game system **118** may not be provided for each seat of the ride vehicle **84**. For example, an on-board game system **118** may instead be provided for a group of seats (e.g., a team of users) or for the ride vehicle **84** as a whole, and the AR/VR experience may be provided via multiple HMDs **92** and/or other types of visual experience generator(s). As another example, the on-board system **88** may be used in an attraction without the ride vehicle **84**, and in such cases, the on-board game systems **118** may be provided for each user or for a group of users.

[0066] The first on-board game system **118A** includes a gaming computer **140** programmed with appropriate game logic, and may incorporate appropriate rendering hardware and software that is capable of being integrated into the on-board game system **118** in a manner that allows rapid maintenance, replacement, and technical refreshes as set forth in FIG. **2**. For example, the gaming computer **140** may include processing circuitry **142** and memory circuitry **144** specially programmed to perform functions associated with graphical rendering and overlay. For example, the gaming computer **140** may include one or more graphics cards.

[0067] By way of example, the processing circuitry **142** and the memory circuitry **144** may include game logic, and may run simulations of the real-world ride vehicle **84** based on, for example, a stored map of the real-world environment, motion profile information, and stage geometry for the placement of virtual objects in real space via the HMDs **92**. Each gaming computer **140** may perform these functions for each on-board game system **118**, or certain functions may be shared across the different gaming computers **140** of the on-board game systems **118**. For example, the gaming computer **140** of the first on-board game system **118A** may render content and perform simulations corresponding to actions of a first user, and the gaming computer **140** of the

second on-board game system **118B** may render content and perform simulations corresponding to actions of a second user. These renderings and simulations may, in certain embodiments, be communicated across on-board game systems **118** to reduce computing time. However, in certain embodiments and as set forth above, the on-board game server **114** may communicate non-processed or minimally processed data to all the on-board game systems **118** to reduce input latency. Further, in certain embodiments, the gaming computers **140** may have more sophisticated programming and communication to allow for information sharing, such as direct memory access capabilities.

[0068] The gaming computer **140** is communicatively coupled by way of communication and power conductors (e.g., hardwired) to the HMD **92**. For example, the HMD **92** may essentially be considered the display corresponding to the gaming computer **140**. Because the gaming computer **140** is able to provide power and communication to the HMD **92**, the HMD **92** does not necessarily require a local power source or local processing circuitry for rendering content. The connections between the gaming computer **140** and the HMD **92** may be made in accordance with any appropriate communications and power standards. For example, the gaming computer **140** may power and/or provide video to the HMD **92** using any appropriate universal serial bus (USB) standard, any appropriate high-definition multimedia interface (HDMI) standard, or other communication, power, and/or connection standard, or any combination thereof. In certain embodiments, the HMD **92** may be tethered to the ride vehicle **84**, and there may be one or more intermediate interfaces between the HMD **92** and the gaming computer **140** located on and/or within the ride vehicle **84**. Such a configuration may be desirable, for example, to allow maintenance to be performed on the HMD **92** (e.g., cleaning between uses by different users **14**) with minimal to no downtime for the ride vehicle **84**.

[0069] The HMD **92**, generally, may be configured to display the AR/VR environment rendered by the gaming computer **140**. In particular, the HMD **92** may include electronic eyeglasses that may include one or more displays configured to allow projection and/or overlay of AR/VR features. The HMD **92** may also include orientation and/or position sensors, such as accelerometer, magnetometer, gyroscopes, GPS receiver, motion tracking sensor, electromagnetic and solid-state motion tracking sensor, IMU, presence sensor, and others. Indeed, in certain embodiments, the HMD **92** may incorporate the tracking sensors **120** set forth in FIG. 4. In accordance with present embodiments, the HMD **92** may receive display signals so that the AR/VR graphics can be shown on the one or more displays.

[0070] The gaming computer **140** may also render content in accordance with identifying information associated with the user **14**. For example, the gaming computer **140** as illustrated is communicatively coupled to an identification system **146**. The identification system **146** is generally configured to read identifying information about the user **14** from a device that is associated with the user **14** (e.g., a personal electronic device, wearable, or the like). For example, the identification system **146** may include radio-frequency identification (RFID), near-field communication (NFC), or any other suitable identification technology to determine the identification of the respective user **14**. For example, the identification system **146** may include an RFID reader to read an RFID tag carried by the respective user **14**

to determine some aspect relating to the user **14**, for example a team association of the user **14** (e.g., team “barn animal” versus team “clown”). In some embodiments, the information detected by the identification system **146** may be used by the gaming computer **140** to generate a personalized game experience by rendering content that is associated with the user’s information. For example, if the user **14** is on team clown, content may be rendered in accordance with a clown theme (e.g., with balloons, cotton candy).

[0071] To provide a more immersive experience, the ride vehicle **84** may also include audio outputs. In the illustrated embodiment, the first on-board game system **118A** includes a digital signal processor (DSP) **148** and one or more audio devices **150**. The audio may be provided in a dedicated manner for each of the users **14**, for example as headphones specific to each user **14**, speakers proximate the head area for each user **14**, and so forth. Additionally or alternatively, the audio may be provided for the entire ride vehicle **84**, but with dedicated signals being provided to each speaker of the ride vehicle **84** to provide for surround sound effects, and so forth. In this respect, the DSP **148** may include corresponding processing circuitry configured to perform digital signal processing to generate audio effects based on instructions from the gaming computer **140**, and to output audio signals to the one or more audio devices **150**. It should be noted that in embodiments where the audio outputs are shared for the entire ride vehicle **84**, there may be only one DSP **148** per ride vehicle **84**, and accordingly all the gaming computers **140** on that ride vehicle **84** may provide inputs to the same digital signal processor **148**.

[0072] In practice of certain embodiments, the gaming computer **140** may receive inputs from a variety of sources, but are generally communicated from the switch **110** and the on-board game server **114** (see, e.g., FIG. 4), unless the inputs are from the identification system **146** or are power signals. Based on the inputs, the gaming computer **140** may process and render graphics to be displayed using the HMD **92**. The gaming computer **140** may also provide audio information to the DSP **148** in concert with rendering of the graphics, to allow the DSP **148** to generate audio signals for the one or more audio devices **150**. The inputs may include information communicated via the on-board game server **114**, such as information useful in generating AR/VR experience for the respective user **14**. The inputs may include, but are not limited to, information related to or indicative of the user’s position, orientation, focal length, gaze direction, field of view, motion, or any combination thereof. The inputs may, additionally or alternatively, include, but are not limited to, information related to or indicative of the ride vehicle’s position, orientation, motion vector, velocity, or any combination thereof.

[0073] The inputs may additionally or alternatively include, but are not limited to, information related to or indicative of the passenger’s user information (e.g., any suitable information provided by or authorized by the user/passenger, such as payment information, membership information), personal information (e.g., age, height, special needs, etc.), gaming information (e.g., information about the AR/VR game associated with themed attractions, information about a particular character the user/passenger is associated with in the AR/VR game, information about game history of the user), or any combination thereof. As may be appreciated, the information detected by the identification system **146** may allow the gaming computer **140** to link or

associate the respective user **14** to a particular portion of the inputs corresponding to data indicative of the user information, personal information, gaming information, or any combination thereof.

[0074] Further still, the inputs may include, but are not limited to, information related to or indicative of the user's engagement or interaction with the AR/VR features, such as operation of handheld controllers, joysticks, push buttons, or any combination thereof of the one or more user interfaces **122**. As such, the gaming computer **140** may generate AR/VR features corresponding to actions applied by the user **14** (e.g., actions in the AR/VR environment, such as shooting a stream of water, grabbing an AR or VR object). The inputs may include, but are not limited to, information related to or indicative of the user's engagement in a shared game (e.g., a game having multiple players). As such, the gaming computers **140** of the on-board game systems **118** engaged in the shared game may coordinate generation and rendering of the AR/VR features, such that the users **14** engaged in the same game may see the same AR/VR features on their HMDs **92**.

[0075] FIG. 6 is a perspective view of an embodiment of the ride vehicle **84**, illustrating an example of various components of the on-board system **88** integrated with the ride vehicle **84**. As noted above, in some embodiments, certain components of the on-board system **88** may be located off of the ride vehicle **84**. In the illustrated embodiment, the ride vehicle **84** may have a body **152** or a frame including a front portion **152A**, a back portion **152B**, a side portion **152C**, and a bottom portion **152D**, all or some of which may be fitted with access panels **153**. For example, the access panels **153** may be formed into a surface of the body **152**. In accordance with present embodiments, the access panels **153** may be used to readily access mechanical features of the ride vehicle **84** and/or features of the on-board system **88**.

[0076] One or more seats or passenger spaces **154** (e.g., four seats) of the ride vehicle **84** are configured to accommodate one or more passengers (users **14**). The ride vehicle **84** may include one or more front panels **156** in front of the one or more seats **154** to allow the users **14** to access various features, such as the user interfaces **122**, HMDs **92**, and so forth. Indeed, at least some of the various components of the on-board system **88** may be integrated with and/or disposed on the ride vehicle **84** in an arrangement as discussed below. However, it should be noted that such an arrangement is provided as an example, and in other embodiments, the arrangement may vary depending at least on the configuration of the ride vehicle **84**.

[0077] In the illustrated example, the on-board game server **114** may be in the front portion **152A** of the body **152**. The on-board game systems **118**, or certain of their respective features, may be in usable proximity of their respective seats **154**. As one particular example, the HMD **92** of the on-board game system **118** may be tethered via a cable or a wire to the front panel **156**. The identification systems **146** and the audio devices **150** of the on-board game systems **118** may also be disposed on or integrated with the front panels **156**.

[0078] Each of the gaming computers **140** may be disposed, for example, in a space or compartment in or below a respective one of the seats **154**. The user interfaces **122** may be integrated with the respective front panel **156** and/or adjacent to the respective seat **154**. As set forth above, each

seat **154** has a dedicated HMD **92**, identification system **146**, audio device **150**, gaming computer **140**, and user interface **122**. The tracking systems **124** may be disposed on or integrated with the ride vehicle **84** at locations suited for the functionality. For example, some of the sensors **120** (e.g., accelerometer, GPS receiver, presence sensor, motion tracking sensor) of the tracking system **124** may be disposed in the front portion **152A** of the body **152**, and some of the sensors **120** (e.g., IMU, gyroscope) may be disposed on or integrated with the HMD **92**. It should be noted that, generally, the various components of the on-board system **88** are integrated with the ride vehicle **84** in a manner such that the various components are readily accessible via the access panels **153** for replacement, modification, maintenance, upgrade, and so forth.

[0079] As set forth above, the on-board system **88** of the ride vehicle **84** communicates via the network **96** with the off-board system **90**. The off-board system **90**, as set forth above, may include a variety of devices that are generally designed to complement the AR and/or VR graphics generated by the on-board game systems **118**.

[0080] FIG. 7 is a block diagram of an embodiment of the off-board system **90** of the modular attraction system **50**. In the illustrated embodiment, the off-board system **90** may be disposed in proximity to or along the ride path **82**. The off-board system **90** may include certain features that perform similar roles to those described with respect to the on-board system **88**. For example, the off-board system **90** may include a network communication device **160** (e.g., a modem) and switch **162** (e.g., a router) that establish a connection with the network **96** and establish a local network between the off-board system components. It should be appreciated that the off-board system **90** may include any suitable communication component(s) that enable communication between the off-board system **90** and the network **96**. The connection between the various components of the off-board system **90** may include a wired and/or wireless communication network, such as WLAN, WWAN, and NFC.

[0081] As shown, the switch **162** is directly connected to an off-board game server **164**, one or more off-board game systems **166**, and a ride show supervisor (RSS) **168**. There may be only one, or a plurality of different off-board game systems **166**, as denoted by an asterisk.

[0082] The RSS **168** may be a programmable logic controller (PLC), or other suitable control device. The RSS **168** may include a processor (e.g., a general-purpose processor, a system-on-chip (SoC) device, an application-specific integrated circuit (ASIC), or some other similar processor configuration) operatively coupled to a memory (e.g., a tangible non-transitory computer-readable medium and/or other storage device) to execute instructions stored in the memory. The RSS **168**, generally, may be configured to coordinate the off-board entertainment experiences using one or more light systems **170**, one or more animatronics **172**, or other props. In particular, the RSS **168** may be communicatively coupled to the one or more light systems **170** and the one or more animatronics **172** to control or regulate their operations. For example, the RSS **168** may control intensity, incident angle, on/off states, color, and other effects of the one or more light systems **170**. The RSS **168** may control movements, on/off states, and other actions (e.g., sound effects, light effects) of the one or more animatronics **172** or other props. In some embodiments, the RSS

168 may control or regulate the operations of the one or more light systems **170** and the one or more animatronics **172** based on the AR/VR experiences rendered by the on-board system **88**, or in coordination with other elements of the off-board system **90**.

[0083] The one or more light systems **170** may include various lights, such as ceiling lights, lamps, wall lights, exterior lights, and so forth. The one or more animatronics **172** may include various robotic devices that emulate certain lifelike movements. Further, while not specifically shown, other props such as automated show effects, may be controlled by the RSS **168** in response to signals received via the switch **162**, for example in coordination with operations of the on-board system **88**.

[0084] The one or more off-board game systems **166** may have a similar configuration to the on-board game system **118** described with respect to FIG. 4. For example, the one or more off-board game systems **166** may each include a processor (e.g., a general-purpose processor, a system-on-chip (SoC) device, an application-specific integrated circuit (ASIC), or some other similar processor configuration) operatively coupled to a memory (e.g., a tangible non-transitory computer-readable medium and/or other storage device) to execute instructions. The one or more off-board game systems **166**, generally, may be configured to provide and coordinate entertainment experiences to the passengers, using the one or more media systems **174**. In particular, the one or more off-board game systems **166** may transmit audio/video data (e.g., via a high-definition multimedia interface (HDMI)) to the media system **174**, and the media system **174** may present the audio/video data via one or more display devices (e.g., projection display devices, digital display devices) and one or more sound devices (e.g., speakers) disposed along the ride path **82**. The one or more off-board game systems **166** may coordinate transmission of the audio/video data and/or control operations of the one or more media systems **174**, such that the audio/video contents are displayed on different media systems **174** in a coordinated/synchronized timing or schedule.

[0085] The off-board game server **164** may be a specially-programmed server computer, a programmable logic controller (PLC), or other suitable control device. The off-board game server **164** may include a processor (e.g., a general-purpose processor, a system-on-chip (SoC) device, an application-specific integrated circuit (ASIC), or some other similar processor configuration) operatively coupled to a memory (e.g., a tangible non-transitory computer-readable medium and/or other storage device) to execute instructions stored in the memory. The off-board game server **164**, generally, may be configured to coordinate communication of various information between the various components of the off-board system **90**, and also between the on-board system **88** and the off-board system **90** over the network **96**.

[0086] In particular, the various information may be routed to the various components of the off-board system **90** via the switch **162**. The switch **162** is generally a router or any suitable networking device that forwards information (e.g., data packets) to destination nodes or computer networks, so as to perform the traffic directing functions on the network. As an example, the off board game server **164** may direct information between the RSS **168** and the one or more off-board game systems **166**, via the switch **162**.

[0087] In addition, the off-board game server **164** may be configured to coordinate or synchronize communication of

information depending on the information types and/or priorities, in a similar manner as the on-board game server **114**. As such, the off-board game server **164** may coordinate or synchronize the communication effectively and ensure communication of important information.

[0088] FIG. 8 is a block diagram of an embodiment of the on-board system **88** and the off-board system **90** that may be used in the modular attraction system **50**. As shown, the on-board system **88** includes the on-board game server **114** and the on-board game systems **118**. The on-board system **88** also includes the VSS **116** and the vehicle show effects **126**, as well as a vehicle control supervisor (VCS) **200**, vehicle controllers/motors **202** (e.g., steering controllers; motors), and vehicle sensors **204**. The vehicle sensors **204** may be an example of the tracking sensors **120** described with respect to FIG. 4. The on-board system **88** may include other features, such as other types of tracking sensors **120** and the tracking systems **124**, and/or the user interfaces **122** of FIG. 4, for example.

[0089] The VCS **200** may be a programmable logic controller (PLC), or other suitable control device. For instance, the VCS **200** may include a processor (e.g., a general-purpose processor, a system-on-chip (SoC) device, an application-specific integrated circuit (ASIC), or some other similar processor configuration) operatively coupled to a memory (e.g., a tangible non-transitory computer-readable medium and/or other storage device) to execute instructions stored in the memory. The VCS **200** may be configured to coordinate various operations and movements of the ride vehicle **84** in response to information and/or instructions provided by other components of the on-board system **88** and by the off-board system **90**. In particular, the VCS **200** may receive signals from the vehicle sensors **204** (e.g., indicative of a position, orientation, velocity, motion vector, or other parameter of the ride vehicle **84**), game information from the on-board server **114** (e.g., via a connection point **206**), and/or other information related to other ride vehicles **84**, off-board show effects **208** (e.g., the light systems **170**, the animatronics **172**). The VCS **200** may then send signals to instruct the vehicle controllers/motors **202** to control the movement of the ride vehicle **84** (e.g., forward and/or rearward movement along the track) based on the received signals and information. In the illustrated embodiments, the VCS **200** is also communicatively coupled to the VSS **116**, such that information may be exchanged between the VSS **116** and the VCS **200**. In this way, the VCS **200** and the VSS **116** may coordinate the vehicle show effects **126** and the movement of the ride vehicle **84**, for example. As shown, signals from the vehicle sensors **204** may also be provided to the on-board game server **114**, which may enable the on-board game server **114** to coordinate the movement of the ride vehicle **84** with other effects or events, such as the game played via the on-board game system **118**.

[0090] In the illustrated embodiment, the off-board system **90** includes the off-board game server **164**, the off-board game systems **166**, and the media system **174**. The off-board system **90** also includes the RSS **168**, off-board show effects **208**, and a ride control supervisor (RCS) **210**. The RCS **210** may be a programmable logic controller (PLC), or other suitable control device. The RCS **210** may include a processor (e.g., a general-purpose processor, a system-on-chip (SoC) device, an application-specific integrated circuit (ASIC), or some other similar processor configuration) operatively coupled to a memory (e.g., a tangible non-

transitory computer-readable medium and/or other storage device) to execute instructions stored in the memory. The RCS **210** may be configured to coordinate various operations and movements of multiple different ride vehicles within the attraction (e.g., along the ride path **82**) in response to information and/or instructions provided by components of the on-board system **88** and/or by other components of the off-board system **90**, for example.

[0091] Various components of the on-board system **88** and the off-board system **90** may be connected to one another as shown by a connection point **206**, which represents various communication connections, power connections, and so forth. For example, some of the communication connections may be achieved via the switch **110**, the network communication device **112**, the switch **162**, and/or the network communication device **160** described herein with respect to FIGS. **4** and **7**. The connection point **206** may generally include a network and related features that enable any of a variety of components of the modular attraction system **50** to communicate with one another (e.g., the RSS **168** and the VSS **116** may communicate via the connection point **206**). While certain connections in FIG. **8** (and other figures) are illustrated (e.g., via connecting lines that may indicate two-way communication and arrows that may indicate one-way communication) between various components of the modular attraction system **50**, it should be appreciated that the components shown and described herein may be connected in any of a variety of ways (e.g., some illustrated connections may be removed and/or some other connections may be added; one-way connections may be two-way connections, and vice versa). Furthermore, while certain components in FIG. **8** (and other figures) are illustrated, it should be appreciated that the some of the illustrated components may be removed and/or some other components may be added. Processing functions discussed herein may also be divided or distributed among the components in various other ways (e.g., some functions of the VSS **116** may be carried out by the on-board game server **114**).

[0092] It should be noted that the modular attraction system **50** includes the on-board system **88** and the off-board system **90**, and each may have its own individually distinct functionality. When these functionalities are combined, they may be used to provide gaming effects and other entertainment to provide an overall experience and to enhance the ride experience. Furthermore, within each of the on-board system **88** and the off-board system **90**, modularity is built in, such that each of the various portions/components of the on-board system **88** and of the off-board system **90** has its individually distinct functionality. While all of these functionalities are controlled and regulated by the modular attraction system **50** in a cooperative and collaborative manner, the individual distinct functionality may be flexibly re-engineered. As such, the engineering (e.g., design, modification, upgrade, maintenance, replacement, etc.) of the overall ride experience may benefit from characteristics of the modular attraction system **50**. In particular, the technical effects may include, but are not limited to, flexibility (scalability, upgradeability, replaceability, convenience in maintenance, quick to deploy, etc.), cost effective (e.g., simplified planning and engineering), and predictability (e.g., easily tested and validated designs).

[0093] While only certain features of the present embodiments have been illustrated and described herein, many modifications and changes will occur to those skilled in the

art. It is, therefore, to be understood that the appended claims are intended to cover all such modifications and changes as fall within the true spirit of the present disclosure. Further, it should be understood that certain elements of the disclosed embodiments may be combined or exchanged with one another.

1. An amusement park system, comprising:

a modular attraction system, comprising:

a ride vehicle having seats to accommodate passengers; and

an on-board system integrated with the ride vehicle and comprising a plurality of game systems connected via a network, wherein each game system of the plurality of game systems is configured to provide an augmented reality (AR) experience, or a virtual reality (VR) experience, or both, via a respective visual experience generator device, and wherein the AR experience, or the VR experience, or both, is provided within a game shared between the plurality of game systems;

wherein the plurality of game systems is integrated into the ride vehicle, and the game systems of the plurality of game systems are connected via the network to one another in a manner that allows for ready removal of at least one game system of the plurality of game systems without affecting operation of remaining game systems of the plurality of game systems.

2. The amusement park system of claim 1, wherein the on-board system comprises an on-board network switch communicatively coupled to each game system of the plurality of game systems separately.

3. The amusement park system of claim 2, wherein the on-board system comprises an on-board game server communicatively coupled to the plurality of game systems via the on-board network switch, wherein the on-board game server is configured to receive passenger input data, and to distribute the passenger input data via the on-board network switch to the plurality of game systems.

4. The amusement park system of claim 3, wherein the visual experience generator devices comprise head mounted displays (HMDs), the on-board system comprises user interfaces and a tracking system configured to track motion, orientation, or both, of the HMDs, and wherein the user interfaces and the tracking system are configured to provide the passenger input data to the on-board game server.

5. The amusement park system of claim 4, wherein the on-board system comprises a vehicle show supervisor (VSS), and wherein the on-board game server is configured to coordinate communication between the tracking system, the plurality of game systems, and the VSS, via the on-board network switch.

6. The amusement park system of claim 5, wherein the on-board game server is configured to communicate with the plurality of game systems and the VSS according to an information hierarchy in which a first type of information is communicated with a higher priority than other types of information.

7. The amusement park system of claim 3, wherein each game system of the plurality of game systems of the on-board system comprises:

a gaming computer communicatively coupled to the on-board game server via the on-board network switch and configured to render graphics for the AR experience, or

the VR experience, or both, based on the passenger input data received from the on-board game server; and the respective visual experience generator device tethered to the ride vehicle and communicatively coupled to the gaming computer, wherein the respective visual experience generator device is configured to display the rendered graphics on one or more display surfaces.

8. The amusement park system of claim 7, wherein each game system of the plurality of game systems comprises an identification recognition system communicatively coupled to the gaming computer and configured to retrieve identifying information relating to a passenger occupying a seat corresponding to the game system, and wherein the gaming computer is configured to render the graphics in accordance with the received identifying information.

9. The amusement park system of claim 1, wherein the modular attraction system comprises an off-board system in communication with the on-board system via the network, wherein the off-board system is configured to provide off-board show effects in coordination with the game shared between the plurality of game systems.

10. The amusement park system of claim 9, wherein the off-board system comprises:

- one or more off-board game systems each comprising an off-board game computer;
- a ride supervisor system (RSS) configured to control show effect devices positioned off of the ride vehicle;
- an off-board network switch communicatively coupled to each of the one or more off-board game systems separately and to the RSS; and
- an off-board game server communicatively coupled to the one or more off-board game systems and to the RSS via the off-board network switch and configured to coordinate communication between the one or more off-board game systems and the RSS.

11. The amusement park system of claim 10, wherein the off-board system comprises one or more media systems disposed off of the ride vehicle and communicatively coupled to the one or more off-board game systems, wherein an off-board gaming computer of each of the one or more off-board game systems is configured to generate media for display by a respective media system of the one or more media systems in coordination with the game shared between the plurality of game systems.

12. The amusement park system of claim 1, wherein the ride vehicle is configured to travel along a ride path.

13. A modular amusement park ride vehicle, comprising:

- a body having a passenger compartment and seats to accommodate passengers;
- a plurality of on-board game systems, wherein each on-board game system of the plurality of on-board game systems is associated with a respective seat to allow each passenger of the modular amusement park ride vehicle to participate in an augmented reality (AR) and/or virtual reality (VR) game shared between the plurality of on-board game systems, wherein each on-board game system of the plurality of on-board game systems comprises a gaming computer configured to render AR and/or VR graphics, and a head-mounted display (HMD) in communication with the gaming computer and configured to display the AR and/or VR graphics;

an on-board game server configured to coordinate communication with the on-board game systems via an on-board network switch individually connected to the on-board game systems of the plurality of on-board game systems; and

- a vehicle show supervisor (VSS) communicatively coupled to the on-board game server and configured to receive game inputs from the passengers relating to the AR and/or VR game and to relay the received game inputs to the on-board game server via the on-board network switch.

14. The modular amusement park ride vehicle of claim 13, comprising an access panel formed into a surface of the body and configured to allow ready access to at least one on-board game system of the plurality of on-board game systems, or the on-board game server, or the VSS.

15. The modular amusement park ride vehicle of claim 13, comprising user interfaces individually communicatively coupled to the VSS, wherein each seat is associated with at least one user interface to allow provision of the game inputs to affect the AR and/or VR game.

16. The modular amusement park ride vehicle of claim 13, wherein each HMD comprises an integrated tracking sensor communicatively coupled to a tracking system, and wherein the tracking system is configured to produce tracking data relating to motion and orientation of the HMD, and wherein the on-board game server is configured to distribute the tracking data to at least an on-board game system of the plurality of on-board game systems corresponding to the seat to which the HMD is associated.

17. The modular amusement park ride vehicle of claim 13, comprising a networking device communicatively coupled to the on-board network switch to allow the on-board network switch to access a network shared between the modular amusement park ride vehicle and other networked devices that are located off-board the modular amusement park ride vehicle.

18. An amusement park attraction system, comprising:

- an on-board system integrated with a ride vehicle, wherein the on-board system has a visual experience generator device for each seat in the ride vehicle, and wherein the on-board system is configured to provide an augmented reality (AR) experience, virtual reality (VR) experience, or both, within a shared game via at least the visual experience generator devices; and
- an off-board system communicatively coupled to the on-board system via a network and having off-board show devices positioned off of the ride vehicle, wherein the off-board system comprises an off-board game server communicatively coupled to the off-board show devices and configured to coordinate operation of the off-board show devices with AR or VR events occurring during the shared game.

19. The amusement park attraction system of claim 18, wherein the on-board system is integrated with the ride vehicle such that the on-board system is configured to move with the ride vehicle along a ride path during a ride in an amusement park.

20. The amusement park attraction system of claim 17, wherein the off-board show devices comprise a light system, an animatronic, or a combination thereof.